Technical data sheet

STEICOmulti primer

Solvent-free primer



Solvent-free primer for porous substrates such as wood fibre boards

- Solvent free
- Can be processed from -10 °C
- High penetration
- Fast flash-off time, good water resistance
- Efficient material application thanks to practical dispenser bottle

Application area



- Adhesion promotion / adhesion improvement of bonds with STEICO-*multi tape*

Technical data

Processing temperature min.	- 10 °C
Basis	aqueous acrylate polymer dispersion
Film property	Flexible (after curing)
Range for 1 kg	+ STEICOmulti tape F 100mm approx. 35 m + STEICOmulti tape F 150mm approx. 25 m m
Storage property (unopened)	12 months
Airing time	~ 14 (at +20°C / 50% relative humidity) min

Forms of delivery

Form of delivery	Weight/piece [kg]	Size [ml]	Number/pack. [pcs.]
Bottle with dispenser	1.10	1000	6

Weight and packing

Weight/m²[kg]	Weight/pcs. [kg]	Weight/pack. [kg]	Packaging/pack. Paper/cardboard (approx.) [kg]
1.00	1.1	7.00	0.30

Technical data sheet

STEICOmulti primer

Solvent-free primer

Notes

Storage

- Store in a cool and dry place at +15 to +25 °C
- Protect from heat, cold and UV radiation

Disposal

- Dispose of hardened material residues according to EWC 17 09 04 (mixed construction and demolition waste)

Application method

- Brush or paint roller

Occupational health and safety

- Additional information in the safety data sheet must be observed.

Installation

- The substrate must be dry and free of grease and dust
- Shake the bottle well before use
- Apply the material to the substrate via the guide opening of the bottle and spread evenly with a brush or paint roller.
- Before applying and pressing on STEICO*multi tape*, allow the STEICO*multi primer* to flash off until transparent (colour change is permitted visual inspection)
- STEICO*multi primer* can be removed with water when fresh. When the primer has hardened, cleaning is generally only mechanically possible

Certificates and quality management

Caption

other abbreviations

pal. Pallet
T&G Tongue and Groove
pac. Packaging
approx. Approximately
EUR Europe

Technical data sheet

STEICOmulti primer

Solvent-free primer

Compliance

Responsible for content
STEICO SE
Otto-Lilienthal-Ring 30
85622 Feldkirchen
Germany
Web: www.steico.com
Mail: info@steico.com

Version: 2
Date: 2026-07-03

Liability disclaimer

The contents of this document have been compiled with the utmost care. However, applicable standards and regulations can change. STEICO accepts no liability for the accuracy, completeness and current applicability of the standards and regulations presented. Always check compliance with standards and regulations and the suitability of our products for the specific intended use, and make any necessary adjustments during installation.

STEICO accepts no responsibility for the completeness, accuracy or quality of information provided by third parties.

Regional document validity: EU*

***Additional Validity Information**

The contents of this document have been prepared in consideration of European product standards and provide a general overview of component structures, construction methods, and installation. Local applicable regulations have not been considered.

The most recent version of this document applies. This version can be found at:
www.steico.com/tds_steicomulti_primer_eur_en