Technical data sheet

STEICO*multi tape F*

High performance tape with special foil



High performance tape with special foil for internal and external use

- Solvent-free
- Can be processed from -10 °C, temperature resistant between -40° and +100°C
- High UV and ageing resistance
- High moisture resistance/ rainproof
- With split release paper for the simple formation of e.g. corner bonds

Application area



- Joint and connection bonding of STEICO wood fibre boards in combination with STEICO*multi primer*
- Joint and connection bonding in the STEICO membrane system
- Connection bonding for STEICO*fix* and STEICO*tri* sub-window sills

Technical data

Temperature resistance	-40 / +100 °C
Processing temperature	> -10; The surface must be dry and free of ice °C
Minimum roof pitch	10 °
Adhesive	Acrylic dispersion, solvent-free
Adhesive backing	UV-stabilised special film with polyester lattice, single-sided adhesion
Colour	Grey
Thickness (without release paper)	~ 0,3 mm
UV resistance	12 months
Peeling strength	fulfilled according to DIN 4108/11
Peel strength after ageing	fulfilled according to DIN 4108/11

Forms of delivery

Length [mm]	Width [mm]	Release liner perforation [mm]	Number/pack. [pcs.]
25000	60	-	10

Roll mit slashed back

Length [mm]	Width [mm]	Release liner perforation [mm]	Number/pack. [pcs.]
25000	60	20/40	10
25000	100	50/50	6
25000	150	75/75	4

Technical data sheet

STEICO*multi tape F*

High performance tape with special foil

Weight and packing

Length [mm]	Width [mm]	Weight/m²[kg]	Weight/pcs. [kg]	Weight/pack. [kg]	Packaging/pack. Paper/cardboard (approx.) [kg]
25000	60	0.65	0.7	7.60	0.60

Roll mit slashed back

Length [mm]	Width [mm]	Weight/m²[kg]	Weight/pcs. [kg]	Weight/pack. [kg]	Packaging/pack. Paper/cardboard (approx.) [kg]
25000	60	0.65	0.7	7.70	0.60
25000	100	1.08	1.1	7.70	0.60
25000	150	1.62	1.8	7.70	0.60

Notes

Storage

- Store in a cool and dry place at +5 to +25 °C
- Protect from heat, cold and UV radiation

Ingredients

- Acrylic dispersion (solvent-free), special film, polyester scrim

Disposal

- dispose with normal construction waste, observe applicable legal guidelines

Cutting

- Sharp knife or other suitable cutting tool

Installation

Application in the STEICO membrane system

- Substrates must be stable, dry and free of dust and grease
- Align STEICO*multi tape F* in the middle, remove the release paper step by step, and rub the adhesive tape vigorously in the process
- Slit release paper facilitates the bonding of corners, as liners can be removed in turn as required
- The adhesive tape must be applied without creases
- If tensile forces occur, the substrate must also be mechanically fastened
- Bonds must not be in standing water. Bonding in sauna and swimming pool construction is also not permitted

Installation on STEICO wood fibre boards

- Pre-treat STEICO wood fibre boards in the bonding area with STEICO*multi primer*
- After sufficient flash-off time (if primer is transparent), apply STEICO*multi tape F*, remove release paper and rub on
- The bonding area per butt joint side must be at least 50 mm.
- To improve adhesion, additional pressing with a paint roller or roofing roller is recommended

Technical data sheet

STEICO*multi tape F*

High performance tape with special foil

Certificates and quality management

Caption

other abbreviations

pal. Pallet
T&G Tongue and Groove
pac. Packaging
approx. Approximately
EUR Europe

Compliance

Responsible for content

STEICO SE
Otto-Lilienthal-Ring 30
85622 Feldkirchen
Germany
Web: www.steico.com
Mail: info@steico.com

Version: 2
Date: 2026-07-03

Liability disclaimer

The contents of this document have been compiled with the utmost care. However, applicable standards and regulations can change. STEICO accepts no liability for the accuracy, completeness and current applicability of the standards and regulations presented. Always check compliance with standards and regulations and the suitability of our products for the specific intended use, and make any necessary adjustments during installation.

STEICO accepts no responsibility for the completeness, accuracy or quality of information provided by third parties.

Regional document validity: EU*

***Additional Validity Information**

The contents of this document have been prepared in consideration of European product standards and provide a general overview of component structures, construction methods, and installation. Local applicable regulations have not been considered.

The most recent version of this document applies. This version can be found at:
www.steico.com/tds_steicomulti_tapef_eur_en