STEICO*multi tape P*

High performance tape with kraft paper



High performance tape with kraft paper for internal use

- Solvent-free
- Temperature resistant between -40° and +100°
- Can be torn by hand
- Sturdy cardboard carrier
- Patches ideal for sealing injection holes

Application area



- Joint and connection bonding in the STEICO membrane system, as on wood-based panels e.g. OSB

Technical data

Temperature resistance	-40 / +100 °C
Processing temperature	+5 °C
Adhesive	Acrylic dispersion, solvent-free
Adhesive backing	Kraft paper with PE protective coating
Colour	White
Thickness (without release paper)	~ 0,3 mm
Peeling strength	fulfilled according to DIN 4108/11
Peel strength after ageing	fulfilled according to DIN 4108/11

Forms of delivery

Length [mm]	Width [mm]	Plaster [mm]	Number/roll [plaster]	Number/pack. [pcs.]
40000	60	-	-	10

Rolls with perforated stickers

Length [mm]	Width [mm]	Plaster [mm]	Number/roll [plaster]	Number/pack. [pcs.]
40000	200	180*180	222	1

Technical data sheet

STEICO*multi tape P*

High performance tape with kraft paper

Weight and packing

Length [mm]	Width [mm]	Weight/m²[kg]	Weight/pcs. [kg]	Weight/pack. [kg]	pac./pal. paper/card-board (approx) [kg]
40000	60	1.09	1.1	11.50	0.50

Rolls with perforated stickers

Length [mm]	Width [mm]	Weight/m²[kg]	Weight/pcs. [kg]	Weight/pack. [kg]	pac./pal. paper/card-board (approx) [kg]
40000	200	3.73	3.7	4.20	0.50

Notes

Storage

- Store in a cool and dry place at +5 to +25 °C
- Protect from heat, cold and UV radiation

Ingredients

- Acrylic dispersion (solvent-free), kraft paper with PE protective coating

Disposal

- dispose with normal construction waste, observe applicable legal guidelines

Cutting

- Sharp knife or other suitable cutting tool

Installation

- STEICO*multi tape P* can only be used indoors
- Substrates must be stable, dry, and free of dust and grease.
- Align STEICO*multi tape P* in the centre, remove the release paper step by step and rub the adhesive tape vigorously in the process
- Apply STEICO*multi tape P* without tension or creases. If tensile forces occur, the substrate must also be mechanically fastened.
- To improve adhesion, especially on wood-based panels, additional pressing with a pressure roller is recommended
- Bonding must not be in standing water. Bonding in saunas and swimming pools is also not permitted.

Certificates and quality management

Technical data sheet

STEICO*multi tape P*

High performance tape with kraft paper

Caption

other abbreviations

pal. Pallet
T&G Tongue and Groove
pac. Packaging
approx. Approximately
EUR Europe

Compliance

Responsible for content
STEICO SE
Otto-Lilienthal-Ring 30
85622 Feldkirchen
Germany
Web: www.steico.com
Mail: info@steico.com

Version: 2
Date: 2026-07-03

Liability disclaimer
The contents of this document have been compiled with the utmost care. However, applicable standards and regulations can change. STEICO accepts no liability for the accuracy, completeness and current applicability of the standards and regulations presented. Always check compliance with standards and regulations and the suitability of our products for the specific intended use, and make any necessary adjustments during installation.

STEICO accepts no responsibility for the completeness, accuracy or quality of information provided by third parties.

Regional document validity: EU*

***Additional Validity Information**
The contents of this document have been prepared in consideration of European product standards and provide a general overview of component structures, construction methods, and installation. Local applicable regulations have not been considered.

The most recent version of this document applies. This version can be found at:
www.steico.com/tds_steicomulti_tapep_eur_en